PCT



HI DE ONTO WE BY DESTRUCTION

TO ALL TO WHOM THESE; PRESENTS; SHALL COME; UNITED STATES DEPARTMENT OF COMMERCE **United States Patent and Trademark Office**

October 30, 1997

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/022,445

FILING DATE: August 6, 1996

PRIORITY DOCUMENT

By Authority of the COMMISSIONER OF PATENTS AND TRADEMARKS

Certifying Officer

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE FEE RECORD SHEET

> 350 GC 08/22/%6 80002445 1 114 150.00 EK PS 150.00 LK P96.1747

PTO-1556 (5/87)

		OBSECTION O			
			Fatont and Tru	APÉ O L DES	9 ATTACES (6-95) 0 441 ALCOS & 61 -0037 TIMENT OF COMMERCE
600	PROVISIO.	NAL APPLICA	TION COVE	R SHEET	
bes a fequest forfil	ing a PROVISIONAL A	PPLICATION under	37 CFR 1.53 (b)(2	<u>) </u>	
P Operat Number	P96,1947	Туре	plus sign (+) inside this b	+ +	
A (A) 2		INVENTOR(s)/APPI	LICANT(a)		
CATE OF THE PARTY	FIRST NAME	MEDDLE INITIAL	RESIDENCE (C	TTY AND ETHER STATE OR PO	OREION COUNTRY)
MAY DINGMAN	Stephen Steven	E.	St. Joseph, Mis St. Joseph, Mis		
	Tit	ILE OF THE INVENTION	(280 characters max)		
'MULTI-LAYER	ED CANNED PET F	**************************************			
		CORRESPONDENCE	: ADDRESS		
	233 South	Robert M. B ILL, STEADMAN h Wacker Drive, 85 Chicago	& SIMPSON th Floor Sears T		
STATE	Illinois	ZIP CODE	60606	COUNTRY	USA
	ENCL	OSED APPLICATION PAR	tTS (check all that apply	,	
	er of Pages 13		☐ Small Eac ☐ Other (sp	ecify)	
		METEOD OF PAYME	NT (check ene)		
The Commissioner is b	ir in enclosed to cover the Provi ereby authorized to charge Deposit Account Number: 08	rional filing fees - <u>-2290</u>		PROVISIONAL FILING PEE AMOUNT (5) \$150.00	
S No.	an agency of the United States	•		the United States Governo	uent.
Respectfully submitted	12/2	·	Date J-	6-96	
YPED or PRINTED	NAME Robert M. Barre	n	REGISTRATIO	N NO. (if appropriate	2) 30,142
Additional invent	ors are being named on se	parately numbered shee	ts attached here to		
Burden Hour Statement. This is time you are required to co to 231, and to the Office of In-	PROVISIONA Jorn is estimated to take 7 hour implete this learn should be sent to formation and Regulatory Affair TO THIS ADDRESS SEND TO	is to complete. Time will vary to the Office of Assistance Que es. Office of Management and	y depending upon the nee sity and Enhancement D Budget (Project 9631-9	ds of the individual case. A ivision, Patent and Trudema 037), Washington, DC 2056	ny commonts on the amount



60/022445 NO5531

Patent Application

Title:

Multi-layered Canned Pet food

Inventors:

S. May

S. Dingman

10

15

20

25

30

35



150-140/022445

NO5531

This invention relates to a canned pet food product which contains layers of different appearance and texture. The invention also relates to a process for producing the canned pet food product.

-1-

Background to the Invention

Canned pet foods are traditionally available in two forms; meat loafs and chunk-type products. The meat loafs are particularly well known. They are usually prepared by comminuting raw meat material and mixing it with water, salt, spices, curing agents, gelling agents and, if necessary, fats to provide a batter. The batter is then heated. The heated batter is then filled into cans to form, after retorting and cooling, a meat loaf.

These meat loaf products are popular because they are easily manufactured, readily digested, very palatable to animals, and are readily formulated to contain necessary nutrients and trace elements. However they are in the form of a uniform, homogeneous mass which lacks the striated and chunky appearance of meat. However, for pet foods, a meat-like appearance can greatly enhance consumer acceptability.

The chunk-type products overcome this difficulty since they are formulated emulsions which simulate the appearance of meat. One example of these formulated emulsions is described in US patent 4,781,939. The formulated meat emulsion described in the patent is produced by first forming a meat emulsion from a meat source. Dry ingredients such as dry proteinaceous materials (for example wheat gluten and soy flour), vitamins, minerals and the like are then mixed into the meat emulsion to provide a viscous emulsion. The viscous emulsion is then run through a high-speed emulsion mill in which the emulsion is rapidly heated to a temperature in the range of 102°C to 118°C. The emulsion leaving the emulsion mill is fed to a holding tube where the protein in the emulsion coagulates to form a solid emulsion product. This solid emulsion product is then cut into chunks. The chunks are highly striated and resemble natural meat chunks in appearance and texture.

15

20

25

30

35

-2-

NO5531

Another example of these formulated emulsions is disclosed in US patent 5,132,137. However, in this process the viscous emulsion is heated to a temperature of 40 to 70°C in the emulsion mill; which is much lower than that in the process disclosed in US patent 4,781,939. The heated emulsion takes longer to coagulate and is therefore held in a holding tube for a longer time. The emulsion is then formed into strands and baked in an oven at a core temperature of 70 to 95°C.

Canned pet food products which are a combination of the meat loafs and the chunk-type products are also known. These products are formed of a matrix of the meat loaf surrounding pieces of formulated emulsion products.

However there is a need for canned pet food products which have new and interesting textures and appearances to further stimulate consumer interest.

Summary of the invention

Accordingly, in one aspect, this invention provides a canned pet food product comprising:

a base layer comprising solid food pieces in a gravy, the gravy comprising about 20% to about 40% of the base layer; and

an upper layer comprising a gelled meat loaf, the gelled meat loaf comprising about 20% to about 80% by weight of the pet food product.

Often, after opening a can of pet food, the consumer shakes the contents out into the pet's bowl or dish. Therefore, what was the base layer becomes the upper layer in the pet's bowl or dish. The consumer is therefore presented with an attractive layer of solid food pieces in a gravy above a clearly defined layer of a gelled meat loaf.

Preferably, the solid food pieces in the base layer are a formulated emulsion product having the striated appearance of natural meat. The formulated emulsion product preferably comprises about 65% to about 95% by weight of a meat material and about 5% to about 35% by weight of a proteinaceous material. If desired, the formulated emulsion product may be in the form of flakes.

NO5531

The gravy preferably comprises water and about 2% to about 8% by weight of a starch; for example about 4% by weight of starch. The starch is preferably a heat sensitive starch such that its viscosity increasing properties are reduced after being heated. In particular, it is preferred that the gravy has an initial viscosity in the range of about 350 to about 1000 centipoise prior to retorting of the can but a lower viscosity after retorting. It is particularly preferred that the gravy have an initial viscosity of about 500 to about 700 centipoise; for example about 600 centipoise.

The base layer preferably has a moisture content of about 60% to about 70% by weight. It is particularly preferred that the base layer has a moisture content of about 62% to about 64% by weight; for example about 63% by weight.

The upper layer preferably has a moisture content of about 70% to about 85% by weight.

During filling, the upper layer preferably has a viscosity in the range of about 2500 to about 4000 centipoise. A viscosity in the range of about 3000 centipoise is particularly preferred.

In another aspect, this invention provides a process for producing a canned pet food product having at least two layers, the process comprising:

filling a base layer comprising solid food pieces in a gravy into a can, the gravy having a viscosity in the range of about 350 to about 1000 centipoise and forming about 20% to about 40% of the base layer;

filling an upper layer into the can, the upper layer comprising a meat batter having a viscosity in the range of about 2500 to about 4000 centipoise and, upon cooling, forming a gelled meat loaf, the meat batter comprising about 20% to about 80% by weight of upper and base layers;

sealing the can; and retorting the sealed can.

Preferably the base layer is filled into the can to provide about 30% to about 50% by weight of the upper and base layers.

5

10

15

20

25

30

15

20

25

30

35

NO5531

In a yet further aspect, this invention provides a canned pet food product having at least two layers and produced according to the process defined above.

Detailed description of the Invention

Embodiments of the invention are now described, by way of example only.

To produce the pet food product, a mixture of solid food pieces in a gravy and a meat batter must be separately prepared.

a) Preparation of the solid food pieces in gravy:

The mixture of solid food pieces in a gravy may be prepared by simply mixing together solid pieces of meat or other material, or both, and a gravy. The meat material may be any suitable meat source, for example, muscular or skeletal meat, meat by-products or a mixture of meat and meat by-products. The meat material may be in the form of chunks or may be in the form of flakes. However, if a meat material is used, it is preferred if the solid food pieces are a formulated emulsion product. Solid pieces of other material may also be used; such as cooked rice grains, pasta or noodles, vegetable pieces, and the like.

If a formulated emulsion product, is used, it may be produced by any suitable procedure, for example the procedures described in US patents 4.781,939 and 5.132,137. In these procedures, a meat material is formed into a meat emulsion; usually by grinding and then emulsifying blocks of the meat material. The meat material may be any suitable source of animal protein; for example the muscular or skeletal meat of mammals, poultry, and fish or meat by-products such as hearts, liver, kidneys, tongue and the like. The exact composition may be selected according to cost and the desired flavor. The meat material conveniently may be in frozen form prior to grinding. Alternatively or in addition, the meat material may be in the form of meat meals such as poultry meal, fish meal, red meat meal and mixtures thereof. Again the exact composition may be selected according to cost and the desired flavor. Mixtures of any of the above may also be used. The emulsification may be carried out in any suitable equipment.

10

15

20

25

30

35

Usually a proteinaceous material is added to the emulsion to improve emulsion stability and binding. The proteinaceous material may be a vegetable or animal protein source; for example wheat gluten, soy flour, soy protein concentrates, soy protein isolates, egg proteins, whey, casein, etc. The exact choice will depend upon availability, cost and palatability. Usually about 5% to about 35% of the proteinaceous material is used.

If desired or required, fats may be added to the emulsion. Usually the amount of fat in the emulsion must be controlled to facilitate processing and to obtain an acceptable product. However, the meat material may well contain the desired amount of fats and hence adjustment may not be necessary. Typically at this stage the emulsion contains a maximum fat level of about 25% by weight. Conveniently, the amount of fat in the emulsion is in the range of about 5% to 15% by weight; more preferably about 7% to about 12% by weight. The mass ratio protein to fat in the emulsion is preferably about 1:1 to about 7:1. If added, the fats may be any suitable animal fats; for example tallow, or may be vegetable fats.

Additional ingredients such as sugars, salts, spices, seasonings, flavoring agents, minerals, and the like may also be added to the emulsion. The amount of additional ingredients used is preferably such that they make up about 1% to about 5% by weight of the formulated emulsion product.

Water may also be added to provide from about 45% to 80% by weight moisture in the emulsion. If sufficient moisture is present in the meat material, water need not be added.

Once mixed, the emulsion is preferably fed through a vacuum stuffer, or similar de-aeration apparatus, to de-aerate the emulsion. This removes air which may otherwise cause disruption of the formulated emulsion product and reduce its meat-like appearance.

The emulsion is then fed to an emulsion mill which subjects the emulsion to rapid mechanical heating and shearing. Any suitable emulsion mill may be used, for example the emulsion mill disclosed in US patent 5,132,137. Other suitable emulsion mills are commercially available under the trade name of

s

10

15

20

25

30

35

-6-

NO5531

Trigonal and may be obtained from Siefer Machinenfabrik GmbH & Co KG, Bahnhofstrasse 114, Postfach 101008, Velbert 1, Germany.

The temperature of the emulsion is raised to the desired coagulation temperature in the emulsion mill in a few seconds. For example, the temperature may be raised to from about 100°C to about 120°C. Alternatively, the temperature may be raised to in the range of about 45°C to about 75°C as described in US patent 5,132,137. Usually the mechanical energy generated in the emulsion mill will be sufficient to heat the emulsion but this may be supplemented by the injection of superheated steam.

The heated emulsion leaving the emulsion mill is then transferred to a holding tube. In the holding tube, the heated emulsion coagulates while moving slowly along the holding tube. The residence time of the heated emulsion in the holding tube is sufficient for the emulsion to have coagulated into a firm emulsion product upon reaching the exit of the holding tube.

The firm emulsion product leaving the holding tube is then transferred to a cutter where it is cut into chunks of size suitable for use in a pet food. The chunks may be subjected to flaking if desired.

The gravy or sauce is produced from water, starch and suitable flavoring agents and should comprise about 20% to about 40% of the mixture of solid pieces and gravy. The amount of starch used is sufficient to provide the mixture of solid pieces and gravy with a viscosity of about 350 to about 1000 centipoise; for example up to about 8% by weight of starch may be used. The starch is preferably such that its viscosity increasing properties break down during retorting of the canned pet food. These starches, which are commonly known as modified starches for filling retorted foods, are commercially available from Staley Manufacturing Company (2200 E. Eldorado Street. Decatur, Illinois 62525, USA) and National Starch and Chemical Company (10 Finderne Avenue, Bridgewater, New Jersey 08807).

In place of, or in addition to, the starch, one or more suitable gums may be incorporated into the gravy. Suitable gums are kappa-carrageenan, locust bean gum, guar gum and xanthan gum.

10

15

30

35

b) Preparation of the meat batter:

The meat batter may be prepared by emulsifying a suitable meat material to produce a meat emulsion. The meat material may be any suitable meat source, for example as described above. Suitable gelling agents, for example gums such as kappa-carrageenan, locust bean gum, guar gum and xanthan gum may be added to the meat emulsion. Usually no more than about 2% by weight of gum is needed.

Additional ingredients such as sugars, salts, spices, scasonings, flavoring agents, minerals, and the like may also be added to the meat emulsion. The amount of additional ingredients used is preferably such that they make up about

0.25% to about 5% by weight of the meat batter.

Water may also be added the meat emulsion to provide from about 70% to about 85% by weight. If sufficient moisture is present in the meat material, water need not be added.

20 The meat emulsion is then neated to a temperature above about 65°C in a mixer-cooker. Steam may be injected into the meat batter if desired. The heated meat emulsion is then again emulsified to provide the meat batter and the meat batter maintained at a temperature above about 60°C until needed. At this stage, the meat batter has a viscosity in the range of about 2500 to about 4000 25 centipoise.

c) Canning:

The mixture of the solid food pieces and gravy and the meat batter are then fed to suitable filling machines; one for filling the solid food pieces and gravy and one for filling the meat batter. For filling the solid food pieces and gravy, a pocket filling is particularly suitable. Pocket fillers are commercially available; for example from Luthi Machinery and Engineering Co., Inc (1726 W. 180th Street, Gardena California. 90248, USA), Carruthers Equipment Company (1815 N. W. Warrenton Drive, Warrenton, Oregon 97146, USA) and Zilli & Bellini SPA (Via Benedetta, 85/A. 43100 Parma, Italy). Suitable filling machines

ì5

20

25

30

35

for filling the meat batter are commercially available from Hema USA Inc (426 W. Universal Circle, Sandy, Utah 84070, USA), PRC (2582 S. Tejon Street, Englewood, Colorado 80110, USA). During filling, the meat batter should be maintained at a temperature sufficient to prevent gelling.

A metered amount of the mixture of the solid food pieces and gravy is fed into each can entering the pocket filler in a defined layer comprising about 20% to about 80% of the volume of the can. The cans are then fed to a separate filling machine for filling the meat batter. A metered amount of the meat batter is then fed onto the mixture of the solid food pieces and gravy. Due to the density and viscosity of the mixture of the solid food pieces and gravy and the density and viscosity of the meat batter, clear and distinct layers are formed in the can. These layers remain clear and distinct during seaming of the cans; despite the rotational movement of the cans. After having cooled, the meat batter will form a firm, gelled meat layer.

The cans are then retorted under conditions sufficient to effect commercial sterilization in the normal manner. Typically the cans are retorted at a temperature of about 115°C to about 125°C for about 30 to 100 minutes. During the retorting operation, the starch in the gravy preferably breaks down such that the previously viscous gravy takes on the appearance of a thin, runny sauce.

The cans therefore contain a product which comprises a lower layer made up of solid pieces of food in a thin sauce and an upper layer of a gelled meat loaf. The layers are clear and distinct and the product is visually attractive once removed from the can.

Example 1

a) Production of solid food pieces in gravy

Blocks of frozen meat made up of beef, pork, poultry, fish and meat byproducts are cut into pieces of about 10 cm in size and the pieces are then ground in a meat grinder. The ground meat is transferred to a mixer in which it is heated to a temperature of about 0°C. After mixing, the ground meat is fed into an emulsifier in which it is emulsified and heated to a temperature of about 20°C.

10

15

20

NO5531

The meat emulsion is then transferred to a mixer. A blend of dry proteinaceous material made up of a mixture of wheat gluten, soy flour and soy protein concentrate is added. Additives in the form of vitamins, minerals, flavoring agents, sugars and salts are then added. At this stage, the emulsion is made up of about 77% by weight of meat materials, about 21% by weight of the proteinaceous material and about 2% additives. The fat content is about 10% by weight and the moisture content is about 55% by weight.

The emulsion, at a temperature of about 35°C, is then pumped to an emulsion mill in which it is rapidly heated up to a temperature of about 107°C. The hot emulsion is ejected from the emulsion mill into a holding tube. The emulsion moves slowly through the holding tube such that it is sufficiently cooled and coagulated upon exiting the tube. The coagulated product leaving the holding tube is then cut into cubes of about 2 cm dimension. The chunks have a highly striated, meat like appearance. The chunks are then cooled and flaked to produce flakes of about 1 to about 2 cm size. The flakes are screened to remove small fragments.

A gravy is then prepared by mixing a modified starch, flavoring and coloring agents, and water. The gravy has a viscosity of about 600 centipoise. The mixture is heated to about 80°C and then blended with the flakes. The gravy provides about 30% by weight of the mixture of solid food pieces and gravy.

Production of meat batter b)

25

30

Blocks of frozen meat made up of beef, pork, poultry, fish and meat byproducts are cut into pieces of about 10 cm in size and the pieces are then ground in a meat grinder. The ground meat is transferred to a mixer and heated. Vitamins, minerals, flavoring agents, salts and about 1% by weight of a gum mixture are added. The mixture is heated to about 75°C under mixing and maintained at this temperature. The meat batter has a viscosity of about 3000 centipoise.



















-10-

NO5531

c) Canning

The mixture of solid food pieces in gravy is then transferred to a pocket filler obtained from Carruthers Equipment Company and filled into cans. The amount of the mixture of solid food pieces in gravy is selected to provide about 40% of the total product weight in the can. The cans are then transferred to a filling machine obtained from PRC. The remaining space in each can is filled with meat emulsion.

The cans are then seamed and retorted. A can is opened and turned out onto a plate. The product has a clearly defined lower layer made up of meat loaf topped by a layer of meat flakes in a thin sauce.

Example 2

15

5

10

20

LESSESSE PROFESSES DOCUMENTARION LINESSES A PROFESSES. PROFESSES AND SESSESSES FRANKAIN

The process of example 1 is repeated except that cooked rice is substituted for the flakes of formulated meat emulsion in the solid food pieces and gravy. A can of the product is opened and turned out onto a plate. The product has a clearly defined lower layer made up of meat loaf topped by a layer of cooked rice in a thin sauce.

15

30

We Claim

- 1. A canned pet food product comprising:
- a base layer comprising solid food pieces in a gravy, the gravy comprising about 20% to about 40% of the base layer; and
 - an upper layer comprising a gelled meat loaf, the gelled meat loaf comprising about 20% to about 80% by weight of the pet food product.
- 2. A product according to claim 1 in which the solid food pieces in the base 10 layer are a formulated emulsion product having the striated appearance of natural meat.
 - 3. A product according to claim 2 in which the formulated emulsion product comprises about 65% to about 95% by weight of a meat material and about 5% to about 35% by weight of a proteinaceous material.
 - A product according to claim 3 in which the formulated emulsion product is in the form of flakes.
- 20 A product according to claim 1 in which the gravy comprises water and about 2% to about 8% by weight of a heat sensitive starch which undergoes a reduction in its viscosity increasing properties during heating.
- 6. A product according to claim 1 in which the gravy has an initial viscosity 25 in the range of about 350 to about 1000 centipoise prior to filling of the base layer into the can.
 - A product according to claim 1 in which the base layer has a moisture content of about 60% to about 70% by weight.
 - A product according to claim 1 in which the upper layer has a moisture content of about 70% to about 85% by weight.
- A product according to claim 1 in which the upper layer has a viscosity in 35 the range of about 2500 to about 4000 centipoise during filing of the upper layer into the can.



10. A process for producing a canned pet food product having at least two layers, the process comprising:

filling a base layer comprising solid food pieces in a gravy into a can, the gravy having a viscosity in the range of about 350 to about 1000 centipoise and forming about 20% to about 40% of the base layer;

filling an upper layer into the can, the upper layer comprising a meat batter having a viscosity in the range of about 2500 to about 4000 centipoise and, upon cooling, forming a gelled meat loaf, the meat batter comprising about 20% to about 80% by weight of upper and base layers;

sealing the can; and retorting the sealed can.

5

10

15

11. A process according to claim 10 in which the base layer is filled into the can to provide about 30% to about 50% by weight of the upper and base layers.

NO5531

Abstract of the Disclosure

A canned pet food product having a base layer and an upper layer. The base layer is formed of solid food pieces in a gravy which makes up about 20% to about 40% of the base layer. The upper layer, which provides about 20% to about 80% by weight of the pet food product, is a gelled meat loaf. The separation between the layers is clear and distinct.

10

5

15

20

25

BMc 2/8/96

30

| Paranta | Andrew | Andrew



